



SHEETROCK® FINITURA

Sheetrock Finitura Fine Finisher



Ready to use extra smooth fine finisher:

- Provides smooth finished surface
- Specially formulated to go over plaster
- Low paint absorption
- Economical

SHEETROCK® FINITURA

Sheetrock Finitura Fine Finisher

Description	Ready mix finishing compound for interior use Sheetrock® Finitura is a smooth fine finisher for interior use. Provides excellent workability with good open time and ensures extra smooth surface with strong bonding onto gypsum board, plaster, concrete, and masonry. The low paint absorption makes Finitura economic solution, especially when designer high-end paints are applied. Surface can be sanded once dry to remove any imperfection.
Application	<p>Sheetrock Finitura is specially formulated for treatment of gypsum plaster, but can be applied to different surfaces with excellent result, as follows:</p> <ul style="list-style-type: none">* Gypsum board* Concrete* Masonry <p>The material can be applied both manually or via airless machine with minimum debit of 4 liters/minute (Graco Mark 5 or similar).</p> <p>Layer of max 3 mm is recommended when applied by hand. When sprayed, the material can be diluted - up to 1 liter of water per 20 kg. Recommended nozzle size 531.</p> <p>For best results, 2 layers of application is recommended especially when covering plaster. Can be applied as finishing layer after skim coating with Sheetrock All Purpose.</p> <p>After application the surface can be sanded, if required. Recommended grid paper № 280 or higher. The temperature of the air and surfaces during application should be min 13° C, max 35° C.</p>
Advantages	<ul style="list-style-type: none">* Ready-mixed formula - no waste. After application rest of the material can be stored in a closed pail* Easy to apply* Extra smooth finished surface* Low paint absorption - reduces paint consumption
Product data	Fine Finisher, vinyl based formula. Suitable for both hand and machine application.
Packaging	25 kg pail 6 kg pail 20 kg bag
Consumption	Depends on the type and quality on substrate surface! Indicative consumption on gypsum plaster: 1 kg/sqm on gypsum board: 0.800 kg/sqm.
Storage	Store Finitura closed in dry and fresh spaces. Storing temperature: 5° <> 30°. Rotate stock on first-in, first out basis. Max storing time: 9 months. Protect from freezing!
Color	White



USG Corporation

www.usg.com/europe

USG Greece
USG Interiors Hellas epe
57022 BPE.
Thessaloniki Po box 1362
Greece
Tel: +30 (2310) 722 197
Fax: +30 (2310) 710 106

USG Deutschland GmbH
Metallstraße 1
D 41751 Viersen
Tel: +49 (0) 2162 9570
Fax: +49 (0) 2162 4461
Email: info-de@usg.com

USG France
Z.I. Nord
9 Rue des Livraindeeres
F 28109 Dreux Cedex
Tel: +33 2 37 38 50 50
Fax: +33 2 37 42 10 72
Email: info-fr@usg.com

USG International Inc.
125 South Franklin Street
PO Box 4470
Chicago IL 60680-4470
USA
Tel: +1 312 606 5840
Fax: +1 312 606 5543