

Uni Walton **PUR**

Specification according to EN 548

Uni Walton PUR 2.5

Uni Walton PUR 3.2

Characteristics	Standard	Unit	Result	
Type of flooring	EN 548		Linoleum with PUR Eco System surface protection	
Thickness of PUR Eco System surface protection		µm	app. 20	app. 20
Pattern			uni colored	uni colored
Backing			Jute fabric	Jute fabric

Safety Criteria

Flammability	EN 13501-1	class	C _{fl} - s1*	C _{fl} - s1*
Slip resistance	BGR 181	group	R9	R9
Dynamic coefficient of friction	EN 13893	class	DS	DS
Impact sound reduction	ISO 140-8	dB	4	6

General properties

Sheet width	EN 426	cm	200	200
Sheet length	EN 426	m	20 - 31	20 - 31
Overall thickness	EN 428	mm	2.5	3.2
Total weight	EN 430	g / m ²	2900	3800
Residual indentation	EN 433	mm	≤ 0.15	≤ 0.15
Colour fastness	ISO 105-B02	rating	6	6
Vertical resistance	EN 1081	Ohm	-	-
Electrical insulation to ground	VDE 0100	kOhm	> 200	> 200
Static electrical charge	EN 1815	kV	app. 2.0	app. 2.0
Thermal resistance	EN 12667	m ² K / W	0.015	0.018
Thermal conductivity	EN 12524	W / m K	0.17	0.17

Classification according to EN 685



Class Domestic - heavy



Class Commercial - very heavy



Class Industrial - general



EN 14041 : 2004
08
1658-CPD-1003

Manufactured by:
Armstrong DLW GmbH
Ludwig-Kaufmann-Str. 13
D-27753 Delmenhorst



Armstrong flooring products are to be installed in full accordance with Armstrong's installation instructions and recognised trade standards. An effective, regular cleaning and maintenance programme is vital for retaining a high appearance level. Armstrong flooring products should only be used as floorcoverings. Note: Armstrong Floor Products reserve the right to amend this specification without giving prior notice. For the latest versions of the technical specifications, check our internet site: www.armstrong.eu

* adhered according to certificate, see www.armstrong.eu/my
After the login/register you find the certificate in the Downloadcenter

ISO 9001

ISO 14001

