

Imperial Texture

Specification according to EN 654


Imperial Texture 3.2mm

Characteristics	Standard	Unit	Result
Type of flooring	EN 654		Semi-flexible PVC tiles
			homogeneous
Plastics basis			Polyvinylchloride
REACH Regulation No. 1907/2006	Article 33	weight %	> 0.1 Benzyl butyl phthalate
Pattern			moire
Safety Criteria			
Flammability	EN 13501-1	class	B _{fl} - s1
Dynamic coefficient of friction	EN 13893	class	DS
Impact sound reduction	ISO 140-8	dB	2
General properties			
Tiles: side length	EN 427	cm	30.5 x 30.5
Amount of tiles		m ² per package	4.18
Overall thickness	EN 428	mm	3.2
Total weight	EN 430	g / m ²	6830
Residual indentation	EN 433	mm	< 0.1
Colour fastness	ISO 105-B02	rating	7
Vertical resistance	EN 1081	Ohm	-
Electrical insulation to ground	VDE 0100	kOhm	> 200
Static electrical charge	EN 1815	kV	≤ 2.0
Thermal resistance	EN 12667	m ² K / W	< 0.17
Thermal conductivity	EN 12524	W / m K	0.25


Classification according to EN 685



Class Domestic - heavy



Class Commercial - very heavy




Class Industrial - general



EN 14041 : 2004
05

Manufactured by:
Armstrong World Industries, Inc
1401 N. Hobbie Avenue
Kankakee IL, 60901
USA



Armstrong flooring products are to be installed in full accordance with Armstrong's installation instructions and recognised trade standards. An effective, regular cleaning and maintenance programme is vital for retaining a high appearance level. Armstrong flooring products should only be used as floorcoverings. Note: Armstrong Floor Products reserve the right to amend this specification without giving prior notice. For the latest versions of the technical specifications, check our internet site: www.armstrong.eu